

Lumolux KE

System of protection	IP67
Series	Ø 70 mm
Length	571 mm - 758 mm
Protection tube	K = PMMA G = Borosilicate glass
Power	36 W
Voltage	24 V / 230 V
Ballast	EVG, built-in
Luminous	2900 Lumen

CHARACTERISTICS

- Traditional machine lamp
- 70 mm diameter - proven concept!
- Different versions - for almost every need
- Easy installation and light-bulb change
- IP 67
- Electronic ballast (EVG)



Lumolux KE



TYPE	PROTEC- TION TUBE	ITEM NO	POWER	LUMINOUS / LUMEN	LENGTH / MM	BALLAST / VOLTAGE
Lumolux KE/236	G	591-050-010	36 W	2900	571	EVG 230 V / 50-60 Hz built-in
Lumolux KE/236	K	591-050-021	36 W	2900	758	EVG 230 V / 50-60 Hz built-in
Lumolux KE/236	G	591-050-022	36 W	2900	758	EVG 230 V / 50-60 Hz built-in
Lumolux KE/436	K	591-056-001	36 W	2900	725	EVG 24 V, DC built-in
Lumolux KE/436	G	591-056-002	36 W	2900	725	EVG 24 V, DC built-in

Our Lumolux-lamps are available in different versions. More information available on request!

TYPES


- Your request is not included? Please contact us!
Our Lumolux KE-lamp is available in various types!

SPARE PARTS




replacement lamp 36 W
TC-L
item no.: 213-920-010


FASTENING with fixing clamp




item no.:
599-001-001




item no.:
599-001-002



item no.:
599-001-003



item no.:
599-001-004



item no.:
599-001-016