

# ***CarLift 150 / 625 G***

# ***CarLift 10 / 404 G***

|                      |                              |
|----------------------|------------------------------|
| System of protection | IP67                         |
| Length               | 638 mm / 403 mm              |
| Protective tube      | ESG = toughened safety glass |
| Power                | 15,12 W / 8,4 W              |
| Voltage              | 24 V/DC                      |
| Luminous             | 1890 Lumen / 1050 Lumen      |
| Item nos.            | 591-153-007<br>591-153-009   |



## **CHARACTERISTICS**

- LED-lamp
- Al-box - robust!
- Plug connection M8, 3-pin
- Inclusive cable set with M8-plug
- Compact form - space-saving installation!
- IP 67

# CarLift 150 / 625 G

## CarLift 10 / 404 G



| TYPE                | COVER PLATE | ITEM NO.    | POWER   | LUMINOUS | LENGTH / MM | VOLTAGE | PLUG    |
|---------------------|-------------|-------------|---------|----------|-------------|---------|---------|
| CarLift 150 / 625 G | ESG         | 591-153-007 | 15,12 W | 1890     | 638         | 24 V/DC | M8-side |
| CarLift 10 / 404 G  | ESG         | 591-153-009 | 8,4 W   | 1050     | 403         | 24 V/DC | M8-side |

### ACCESSORIES



Power supply stabilized  
Power: 30 W  
item no. : 213-820-212  
Voltage: 100-240 V / 50-60 Hz /  
24 V/DC

### DRAWING

