

Pendant stations


PLB Series pendant stations for control circuits

Double row IP65 



TECHNO-LIFTING EQUIPMENT

	N° PUSH BUTTONS	DESCRIPTION	CODE	WEIGHT gr
	2+2	For single-speed motor control 2 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB04	560
	2+2	For two-speeds motor control 2 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB04D2	590
	4+2	For single-speed motor control 4 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB06	560
	4+2	For two-speeds motor control 4 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB06D2 PLB06D4	690 720
	6+2	For single-speed motor control 6 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB08	840
	6+2	For two-speeds motor control 6 Mechanically interlocked between pairs + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	■ PLB08D2 PLB08D4 PLB08D6	870 900 1.030
		For single-speed motor control N° mechanically interlocked between pairs	■	
	8+2	8 + 1 Start/Alarm + N° 1 Emergency stop EN ISO 13850 mushroom Ø 30 turn to release	PLB10	1.150
	10+2	10	PLB12	1.270
	12+2	12	PLB14	1.390



DIMENSIONS

N° PUSH BUTTONS	CODE	Amm	Bmm
4	PLB04	345	185
6	PLB06	399	239
8	PLB08	453	293
10	PLB10	547	347
12	PLB12	601	401
14	PLB14	655	455

For the push buttons designation and symbols please see pag. 20-21

Push buttons colours:

 Black and White

 Start/Alarm Green

 Emergency Red

■ For the push buttons designation and symbols please see pag. 20-21