

Technical data
ESW[®]-Compact-001

operating voltage	24V DC $\pm 5\%$
current input	max. 100mA
temperature range	0 to 65°C
type of protection	IP 68
case	high grade steel 1.4571
case dimensions	see Case Drawing
torque	max. 30Nm, power transmission only at hexagonal bolt
weight	1.290g
sight glass	Plexiglass DIN 4102 IB2, s = 5mm
connection cable	2m, SD 90 C, 7 x 0.34mm ² , with shield, cover material: PUR min. bending radius: 20cm
screw-type conduit fitting	M16x1,5 Brass CuZn39Pb3, nickel-plated Lamellar insert: Polyamide PA6 V-2 Sealing ring: Polychloroprene-Nitrile rubber CR/NBR O-Ring: Nitrile rubber NBR
sensor	integrated acceleration sensor
measured value	vibration velocity in mm/s
measurement range	0 to 10 / 0 to 20 / 0 to 50mm/s, switchable
signal assessment	RMS
frequency range	10Hz to 1kHz (-3dB)
filter	Butterworth, 60dB/dec resp. 18dB/oct
analog output	0 to 20mA or 4 to 20mA current source proportional to the selected measuring range
load	max. 390Ohm
switching output	two potential free switching-contacts (30V, 1A)
switching threshold	10% to 100% of measuring range, adjustable by Potentiometer in the case
switching delay	rise time delay K1 = 10s, K2 = 5s fall time delay K1 = 0,5s, K2 = 0,5s
line monitoring	The switching contacts of K1 and K2 are closed in their normal position, the relays are activated (excited). In the case of alarm, voltage drop or cable breakage, the switching outputs become highly resistive because the switching contacts are deactivated.
cable connection	pink +Ub yellow closer contact K1 white closer contact K2 grey analog output blue ground green middle contact K1 brown middle contact K2

Technical data under reservation!

document: hol600_001_td_e.doc date: 02.03.09

ESW[®] is a registered trademark of holthausen elektronik GmbH, Wevelinghoven 38, 41334 Nettetal