

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253

Version 4.0

Revision Date 2015/03/05



Print Date 2015/03/05

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PURITY™/MC FG SPRAY

Synonyms : Purity FG MF Lubricant

Product code : PFMF, PFMFA12

Manufacturer or supplier's details  
Petro-Canada America Lubricants Inc.  
115N Oak Park Avenue #1C  
Oak Park IL 60301-1366  
United States

Emergency telephone number : Suncor Energy: +1 403-296-3000;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

### Recommended use of the chemical and restrictions on use

Recommended use : Purity FG Spray is an advanced multipurpose food grade lubricant in an aerosol can.  
NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.

Prepared by : Product Safety: +1 905-804-4752

---

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

<b>WARNING</b>	
Appearance	Aerosol containing a liquefied gas
Colour	Purity FG Lubricant is clear and bright.
Odour	Hydrocarbon or petroleum oil like.

#### GHS Classification

Flammable aerosols : Category 1

Simple Asphyxiant :

#### GHS Label element

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.  
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. -  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after  
use.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to  
temperatures exceeding 50 °C/ 122 °F.

### Potential Health Effects

Primary Routes of Entry

: Eye contact  
Inhalation  
Skin contact

Inhalation

: At high concentrations, the propellant is a simple asphyxiant and displaces oxygen from the breathing atmosphere. Lack of oxygen may cause CNS depression characterized by dizziness, headaches, nausea, vomiting, fatigue, light-headedness and reduced coordination. Severe overexposure may lead to a coma and/or possible death. Prolonged or repeated inhalation of mist or vapours may cause irritation of the respiratory tract.

Skin

: May cause skin irritation.

Eyes

: May cause eye irritation.

Ingestion

: No known significant effects or critical hazards.

Aggravated Medical Condition

: None known.

### Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

---

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

#### Hazardous components

Chemical Name	CAS-No.	Concentration (%)
petroleum gases, liquefied, sweetened	68476-86-8	25 %
propane	74-98-6	10 - 20 %
isobutane	75-28-5	5 - 10 %

---

### SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.

In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash contaminated clothing before reuse.  
Seek medical advice.

In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.

If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.

Most important symptoms and effects, both acute and delayed : First aider needs to protect himself.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

	Carbon dioxide (CO <sub>2</sub> ) Foam Water fog. Water spray
Unsuitable extinguishing media	: No information available.
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), phosphorus oxides (PO <sub>x</sub> ), carbonyl halides, smoke and irritating vapours as products of incomplete combustion.
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus and full protective wear. Wear a positive-pressure supplied-air respirator with full facepiece.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas.
Environmental precautions	: If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Prevent further leakage or spillage if safe to do so. Use explosion-proof ventilation equipment. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Remove all sources of ignition. Contact the proper local authorities.

---

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Use only with adequate ventilation. Smoking, eating and drinking should be prohibited in the application area. Avoid contact with skin, eyes and clothing. Do not ingest. Do not breathe vapours or spray mist. Use explosion-proof equipment. Wear suitable protective equipment.
-------------------------	--

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
isobutane	75-28-5	TWA	800 ppm 1,900 mg/m3	NIOSH REL

**Engineering measures** : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.  
Use explosion-proof ventilation equipment.

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection  
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0 Revision Date 2015/03/05 Print Date 2015/03/05

Eye protection	: Wear face-shield if splashing hazard is likely.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	: Wash contaminated clothing before re-use.
Hygiene measures	: Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: Purity FG Lubricant is clear and bright.
Odour	: Hydrocarbon or petroleum oil like.
Odour Threshold	: No data available
pH	: No data available
Pour point	: -12 °C (10 °F)Purity FG Lubricant:
Boiling point	: No data available
Flash point	: -104 °C (-155 °F) Propellant:
Fire Point	: No data available
Auto-Ignition Temperature	: No data available
Evaporation rate	: No data available
Flammability	: Extremely flammable aerosol. Propellant is a flammable gas. Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back.
Upper explosion limit	: 9.5 % (V) Propellant:
Lower explosion limit	: 1.8 % (V) Propellant:
Vapour pressure	: No data available
Density	: 0.862 kg/l (15 °C / 59 °F) Purity FG Lubricant:
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

---

Viscosity, kinematic	: 151 cSt (40 °C / 104 °F) Purity FG Lubricant: 19.8 cSt (100 °C / 212 °F) Purity FG Lubricant:
Explosive properties	: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Container explosion may occur under fire conditions or when heated. Ruptured cylinders may rocket.

---

## SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	: Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Reactive with oxidising agents, reducing agents, acids, alkalis, liquid oxygen and alkali metals and their hydroxides.
Hazardous decomposition products	: May release CO <sub>x</sub> , NO <sub>x</sub> , SO <sub>x</sub> , PO <sub>x</sub> , carbonyl halides, smoke and irritating vapours when heated to decomposition.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Eye contact Inhalation Skin contact
--	---

### Acute toxicity

#### Product:

Acute oral toxicity	Remarks: No data available
Acute inhalation toxicity	Remarks: No data available
Acute dermal toxicity	Remarks: No data available

#### Components:

##### **isobutane:**

Acute inhalation toxicity	LC50 (Rat): 658,000 mg/m <sup>3</sup> Exposure time: 4 h Test atmosphere: gas
---------------------------	---

### Skin corrosion/irritation

#### Product:

Result: No skin irritation

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

### **Serious eye damage/eye irritation**

#### **Product:**

Result: No eye irritation

Remarks: There is no data available for this product.

### **Respiratory or skin sensitisation**

No data available

### **Germ cell mutagenicity**

No data available

### **Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to bacteria : Remarks: No data available

### **Persistence and degradability**

#### **Product:**

Biodegradability : Remarks: No data available

### **Bioaccumulative potential**

#### **Components:**

##### **isobutane**

Partition coefficient: n-octanol/water : log Pow: 2.76

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

---

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

### **Product:**

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

## SECTION 14. TRANSPORT INFORMATION

### **International Regulation**

#### **IATA-DGR**

UN/ID No. : 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not Assigned  
Labels : 2.1  
Packing instruction (cargo aircraft) : 203

#### **IMDG-Code**

UN number : 1950  
Proper shipping name : AEROSOLS, LIMITED QUANTITY  
Class : 2.1  
Packing group : Not Assigned  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

### **49 CFR**

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253



Version 4.0

Revision Date 2015/03/05

Print Date 2015/03/05

UN/ID/NA number : 1950  
Proper shipping name : Aerosols  
Class : 2.1  
Packing group : Not Assigned  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

### Special precautions for user

Not applicable

## SECTION 15. REGULATORY INFORMATION

**OSHA Hazards** : Compressed Gas, Flammable aerosol


**The components of this product are reported in the following inventories:**

DSL	On the inventory, or in compliance with the inventory
TSCA	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
IECSC	On the inventory, or in compliance with the inventory
EINECS	On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	H

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

#### For Copy of (M)SDS

: Internet: [lubricants.petro-canada.ca/msds](http://lubricants.petro-canada.ca/msds)  
United States, telephone: 1-800-268-5850; fax: 1-800-201-6285  
For Product Safety Information: 1 905-804-4752

#### Prepared by

: Product Safety: +1 905-804-4752

# SAFETY DATA SHEET

## PURITY™/MC FG SPRAY

000003001253

Version 4.0

Revision Date 2015/03/05



Print Date 2015/03/05

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.