


## **Raychem** GM-2CW; GM-4CW

### CONSTANT WATTAGE HEATING CABLE FOR SNOW MELTING ON ROOFS AND IN GUTTERS

#### HEATING CABLE CONSTRUCTION



#### PRODUCT DESCRIPTION

Raychem GM-2CW and GM-4CW heating cables are roof and gutter snow melting systems which provide solutions for the following applications:

- Roofs made of standard roofing materials including shingle, wood, metal, and plastic.
- Gutters made of standard materials including metal, plastic, and wood.
- Down pipes made of standard materials including metal and plastic.

The heating element of GM-2CW and GM-4CW heating cables consists of 2 conductors with ETFE electrical insulation, an inner jacket extruded with polymer material and a UV resistant LSZH outer jacket.

#### PRODUCT FEATURES

The heating cable is designed according to IEC EN 62395 and available with a LSZH – polymer outer jacket that provides maximum abrasion, chemical, and mechanical resistance; more economical for less demanding applications.

- Low install cost

The GM-2(4) CW heating cables are available in kits of varying pre-terminated lengths with different ohm resistances. The kits include a cold lead connection and end seal. The heating cable can be ordered in two different voltage ranges, 230 V or 400 V AC.

**TECHNICAL SPECIFICATION**

Product description and order reference	GM-2CW-XXM; GM-4CW-XXM
Power output (nominal)	30 W/m
Supply voltage	GM-2CW -> 230 VAC +/- 10% GM-4CW -> 400 VAC +/- 10%
Max circuit length	GM-2CW: 16 A -> 100 m GM-4CW: 20 A -> 215 m
Minimum installation temperature	-5°C
Maximum exposure temperature	80°C
Outer diameter	Max. 6.9 mm
Cold lead	length: 5 m; 3x 1.5 mm <sup>2</sup> , 3 x 2.5 mm <sup>2</sup>
<b>Material</b>	
Inner jacket	HDPE
Braid	Tinned copper wires
Outer jacket	LSZH
Wire insulation	ETFE
Weight	0.046Kg/m -0.071Kg/m
Minimum bending radius	6 x d mm
Deformation strength	1500 N
Connection kits	Raychem junction box JB -16; cold lead and end seal are pre-terminated
Approvals	CE mark, EAC; IEC/EN 62395-1 -2013, Ed2.

**AVAILABLE SIZES AND PART NUMBERS**

PTM Product description	PTM Part number	Voltage	Power Output	Circuit breaker size
GM-2CW-10m	SZ18300097	230 V	300 W	10 A
GM-2CW-15m	SZ18300098	230 V	450 W	10 A
GM-2CW-20m	SZ18300099	230 V	600 W	10 A
GM-2CW-25m	SZ18300100	230 V	750 W	10 A
GM-2CW-30m	SZ18300101	230 V	900 W	10 A
GM-2CW-35m	SZ18300102	230 V	1050 W	10 A
GM-2CW-40m	SZ18300103	230 V	1200 W	10 A
GM-2CW-45m	SZ18300104	230 V	1350 W	10 A
GM-2CW-50m	SZ18300105	230 V	1500 W	10 A
GM-2CW-60m	SZ18300106	230 V	1800 W	10 A
GM-2CW-70m	SZ18300107	230 V	2100 W	10 A
GM-2CW-80m	SZ18300108	230 V	2400 W	16 A
GM-2CW-90m	SZ18300109	230 V	2700 W	16 A
GM-2CW-100m	SZ18300110	230 V	3000 W	16 A
GM-2CW-125m	SZ18300111	230 V	3750 W	20 A
GM-2CW-150m	SZ18300112	230 V	4500 W	20 A
GM-2CW-180m	SZ18300113	230 V	5400 W	25 A
GM-4CW-20m	SZ18300114	400 V	600 W	10 A
GM-4CW-35m	SZ18300115	400 V	1050 W	10 A
GM-4CW-70m	SZ18300116	400 V	2100 W	10 A
GM-4CW-110m	SZ18300117	400 V	3300 W	10 A
GM-4CW-145m	SZ18300118	400 V	4350 W	16 A
GM-4CW-170m	SZ18300119	400 V	5100 W	16 A
GM-4CW-190m	SZ18300120	400 V	5700 W	16 A
GM-4CW-215M	SZ18300121	400 V	6450 W	20 A

Pentair Thermal Building Solutions requires the use of a 30mA residual current device (RCD) to provide the maximum safety and protection from fire. All heating circuits have to be protected by a type C circuit breaker.



[WWW.PENTAIRTHERMAL.COM](http://WWW.PENTAIRTHERMAL.COM)

**UNITED KINGDOM**

Tel: 0800 969 013  
Fax: 0800 968 624  
[salesUK@pentair.com](mailto:salesUK@pentair.com)

**IRELAND**

Tel: 1800 654 241  
Fax: 1800 654 240  
[salesIE@pentair.com](mailto:salesIE@pentair.com)

**SOUTH EAST ASIA**

Tel: +65 67685800  
Fax: +65 67322263

**AUSTRALIA**

Tel: +61 2 97920250  
Fax: +61 2 97745931  
[ausalesthermal@pentair.com](mailto:ausalesthermal@pentair.com)

**INDIA - NOIDA**

Tel: +91 120 464 9500  
Fax: +91 120 464 9548  
[PTMinfome@pentair.com](mailto:PTMinfome@pentair.com)

**INDIA - MUMBAI**

Tel: +91 22 6775 8800/01  
Fax: +91 22 2556 1491  
[PTMinfome@pentair.com](mailto:PTMinfome@pentair.com)

**UAE**

Tel: +971 4 378 1700  
Fax: +971 4 378 1777  
[PTMinfome@pentair.com](mailto:PTMinfome@pentair.com)

Pentair is owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

© 2015 Pentair.

