


Frost protection for pipes

RayClic-LE-02



RayClic with illuminated end seal


- For visual representation of voltage (by green lamp)
- 1 retaining bracket
- IP 68
- External dimension: L = 240 mm
W = 64 mm
H = 47 mm

Note: RayClic components are not compatible with FS-C-2X/FS-C10-2X

9. Accessories for FS-C-2X, FS-C10-2X and BTV-2-CT cables

			For BTV-2-CT				For FS-C-2X/ FS-C10-2X		
Power connection	1 JB16-02	+	1 C25-21	+	1 E-06	+	1 CE20-01	+	JB-SB-08
Splice	1 JB16-02	+	2 C25-21	+	1 E-06	+	2 CE20-01	+	JB-SB-08
Powered splice	1 JB16-02	+	2 C25-21	+	2 E-06	+	2 CE20-01	+	JB-SB-08
T-connection	1 JB16-02	+	3 C25-21	+	2 E-06	+	3 CE20-01	+	JB-SB-08
Powered T-connection	1 JB16-02	+	3 C25-21	+	3 E-06	+	3 CE20-01	+	JB-SB-08
Four way connection	1 JB16-02	+	4 C25-21	+	3 E-06	+	4 CE20-01	+	JB-SB-08


JB16-02



Temperature-resistant junction box

- For FS-C-2X, FS-C10-2X and BTV-2-CT
- For power connection or T-connection
- IP66
- 6 x 4 mm² terminals
- 4 Pg 11/16, 4 M20/25 knock-out entries


JB-SB-08



Single-leg support bracket

- for junction and connection box JB16-02

CE20-01



Connection and end seal kit for FS-C-2X/FS-C10-2X cables

- Heat-shrink technique
- M20 gland