



PRESSURE SWITCH C/W ELECTRICAL CONNECTOR;

SENSOR CAPACITY: MAX SYSTEM PRESSURE 207 BAR (3000 PSI)
PROOF PRESSURE 621 BAR (9000 PSI)

CYCLING: NOT TO EXCEED 30 CPM

ELECTRICAL RATING: 28 V.D.C 5 AMP RESISTIVE
3 AMP INDUCTIVE

CONNECTIONS: COMMON EARTH
OPEN UNDER PRESSURE 1
CLOSED UNDER PRESSURE 2

TEMPERATURE RANGE: -54°C TO +107°C

CONSTRUCTION: ST. ST. HOUSING, BLACK NYLON CAP

WEIGHT: 110 GRAMS APPROX.

SETTINGS: FACTORY SET AT 50 BAR (725 PSI) DECREASING

PRESSURE SWITCH IS TO BE FITTED AT FACTORY CANNOT BE SUPPLIED SEPARATELY

K62462A STANDARD WITH PRESSURE SWITCH

K62959A FM WITH PRESSURE SWITCH

MARKED IN ACCORDANCE WITH 99/36/EC

ALL DIMENSIONS IN mm's UNLESS OTHERWISE STATED

1	29.05.12	ORIGINAL ISSUE	
REV	DATE	REASON FOR ISSUE	APP
DESCRIPTION PRESSURE SWITCH FOR THE N2 PILOT CYLINDER			
PART NO:	SEE DRG.	DS K97699	

Kidde
Fire Protection

Thame Park Road,
Thame,
Oxfordshire, OX9 3RT

Kidde CO2
SYSTEMS