





- PNP
- Normally open (NO)
- 2.50 mm
- Non embeddable
- Connector, M12x1-S04

**General attributes**

Approvals / Conformity

Basic standard
Enclosure Type per IEC 60529
Function indicator
Polarity reversal protected
Power indicator
Protection Class
Short circuit protected

cULus
CE
EAC
IEC 60947-5-2
IP68 according to BWN PR 20
Yes
Yes
No
II
Yes

Electrical attributes

Connection type
Eff. operating current I_e
Eff. operating voltage U_e DC
Electrical version
Load capacitance max. (at U_e)
Max. no-load cur. I_o undamped
Minimum operating current I_m
No-load current I_o damped max.
Operating voltage U_B max. DC [V]
Operating voltage U_B min. DC [V]
Rated insulation voltage U_i

Connector
200 mA
24.0 V
DC, direct current
0.500 μ F
3.0 mA
0 mA
9.0 mA
30.0 V
10.0 V
250 VAC

Rated short circuit current
Ripple max. (% of U_e)
Switching freq. f max. (at U_e)
Switching function
Switching output
Voltage drop static max.

100 A
15 %
2000 Hz
Normally open (NO)
PNP
2.5 V

Mechanical attributes

Ambient temperature T_a max.
Ambient temperature T_a min.
Assured operating distance S_a
Connector type
Depth
Diameter d_1
Eff. operating distance S_r
Housing material
Mech. installation condition
Mounting length
Rated operating distance S_n [mm]
Sensing face material
Tightening torque

70 °C
-25 °C
2.00 mm
M12x1-S04
58.0 mm
M08x1
2.50 mm
Stainless steel
Non embeddable
43.0 mm
2.50 mm
PBT
8 Nm

Additional text

The sensor is functional again after the overload has been eliminated.

