

# Pendant stations




Hoist control: **P02 P03 HP03 DC30**

LIFTING EQUIPMENT

### Characteristics:

- ☐ Bi-directional, mechanically interlocked
- ☐ IP 65 double insulation IEC/EN60529 ☐
- ☐ General and electrical data page 23
- ☐ Laser engraved symbols comply with EN60204-1, FEM 9.941
- ☐ Shock proof and heat resistant



P02

KIT Available See pg. 18  
Available in UL/CSA req.



P03

KIT Available See pg. 18  
Available in UL/CSA req.



HP03

Available in UL/CSA req.



DC30



| PICTURE | LAYOUT | CONFIGURATION                                                                                                   | CODE           | CONTACT TYPE | WEIGHT [gr] |
|---------|--------|-----------------------------------------------------------------------------------------------------------------|----------------|--------------|-------------|
|         |        | SINGLE SPEED<br>(* TILTING BUTTON<br>16A – 250Vac ½ HP)                                                         | <b>P02.RM</b>  |              | 230         |
|         |        | SINGLE SPEED                                                                                                    | <b>P02.1</b>   |              | 230         |
|         |        |                                                                                                                 | <b>P02.2</b>   |              | 250         |
|         |        |                                                                                                                 | <b>P02.4</b>   |              | 250         |
|         |        | (*) HIGH POWER CONTACTS<br>DIRECT MOTOR CONTROL<br>1Kw 1ph                                                      | <b>P02.CD</b>  |              | 230         |
|         |        | TWO SPEED                                                                                                       | <b>P02.D2</b>  |              | 250         |
|         |        | SINGLE SPEED                                                                                                    | <b>P03.1</b>   |              | 440         |
|         |        |                                                                                                                 | <b>P03.2</b>   |              | 450         |
|         |        |                                                                                                                 | <b>P03.3</b>   |              | 460         |
|         |        |                                                                                                                 | <b>P03CD</b>   |              | 460         |
|         |        | TWO SPEED                                                                                                       | <b>P03D2</b>   |              | 460         |
|         |        | SINGLE SPEED                                                                                                    | <b>HP03</b>    |              | 330         |
|         |        | TWO SPEED                                                                                                       | <b>HP03.D2</b> |              | 350         |
|         |        | SINGLE SPEED                                                                                                    | <b>DC30</b>    |              | 600         |
|         |        |                                                                                                                 | <b>DC30.RG</b> |              | 600         |
|         |        |                                                                                                                 | <b>DC30.GE</b> |              | 600         |
|         |        | TWO SPEED<br>(* Ith 25A EXTRA HIGH POWER<br>CONTACTS BLOCK FOR<br>DIRECT MOTOR CONTROL :<br>2.2kW 1ph / 4kW 3ph | <b>DC30D2</b>  |              | 650         |