

Mounting Orientation	Vertical
API Standard 610	Yes
P-Base Diameter	10 in - LP
Thrust Type	Medium - LP
Thrust Direction	Down
P-Base Thrust Req'd	280.00
P-Base B10 Bearing Life	50,000 Hrs (5.7 Yrs)
Vertical Lifting Required	Yes
Shaft Extension	LP

## BEARINGS

Drive End Seal	Slinger
Opposite Drive End Seal	Slinger
Lube Type	Grease
Grease Type	Exxon Polyrex EM
Grease Fittings Rqd	Yes
Grease Fitting Type	Alemite 1610 or equal
Grease Relief Fittings Rqd	Yes
Relief Fitting Type	Alemite

## MECHANICAL

Balance	Standard
Rotation Facing ODE	Bi-directional
Ingress Protection	IP55
Drip Cover Required	Yes
Drip Cover Type	Footless with Vert. Lifting
Paint System	Standard (C2)
Paint Color Specification	Standard Epoxy
Paint Color	Dark Charcoal Gray
Baldor Paint Spec No	004824-007CCV / MG1025G29
Frame Grounding Required	Yes
Ground Pad Type	Drilled & Tapped Hole in Frame
Ground Pad Location	Frame - same side as main CB

## MONITORING DEVICES

Winding Thermostat	Yes
Winding Thermostat Type	High Limit
Thermostat High Limit Contacts	Normally Closed
Winding Thermostat Qty	3 Total - One per Phase
Wdg Thermostat To Main Cbox	Yes

## CONDUIT BOX

Main Conduit Box	Required
Main Conduit Box Location	Standard (side)
Main Conduit Box Material	Cast Iron
Main Conduit Box Size	Standard Oversize
Lead Entry Location	Toward Feet - Down
Grounding	Yes
Ground Servit Post	No
Sealed Leads	Yes