




ProSafe[®] Wireless-N 8-port Gigabit VPN Firewall

- Securely connects up to 5 remote office or traveling users to your office network via VPN
- Stateful packet inspection firewall for robust business security
- IPsec VPNs connect remote users as well as remote sites, with optional software
- Gigabit Networking Ethernet ports offer 10x the speed of Fast Ethernet
- SSL VPNs connect remote users without the need for additional software


Features

- True firewall using stateful packet inspection (SPI) and intrusion detection
- Initiates up to 12 VPN tunnels simultaneously
- IPsec VPN connections using (128-bit, 256-bit) AES and 168-bit 3DES encryption
- NAT routing and VPN pass-through for extra security
- IPV4/IPV6 support
- Application layer gateway support (SIP and FTP)
- Smart Wizard[®] connects to your ISP quickly and easily
- Windows[®], UNIX[®], Macintosh[®] and Linux compatible
- Integrated 8-port 10/100/1000 Gigabit Ethernet switch
- 5 SSL VPN connections
- 64 VLAN support
- b/g/n wireless 2.4Ghz with multiple SSID support



Features	ProSafe 8-port Gigabit VPN Firewall (FVS318N)	ProSafe Dual WAN SSL VPN Firewall (FVS336G)	ProSafe Quad WAN SSL VPN Firewall (SRX5308)	ProSafe Gigabit VPN Firewall (FVS318G)
Ports	(8) 10/100/1000 LAN (1) 10/100/1000 WAN	(4) 10/100/1000 LAN (2) 10/100/1000 WAN	(4) 10/100/1000 LAN (4) 10/100/1000 LAN	(8) 10/100/1000 LAN (1) 10/100/1000 LAN
WAN Redundancy		●	●	
VPN Tunnels	12 IPSEC 5 SSL	25 IPsec 10 SSL	125 IPsec 50 SSL	5 IPsec
LAN-WAN Throughput	95 Mbps	60 Mbps	924 Mbps	25 Mbps
Concurrent Connections	6000	10,000	200,000	6,000
IKE Support	●	●	●	●
Encryption	DES, 3DES, AES	DES, 3DES, AES	DES, 3DES, AES	DES, 3DES, AES
Wireless 802.11 b/g/n	Yes	No	No	No
SIP Aware	●	●	●	●
NAT Routing	●	●	●	●
Classical Routing	●	●	●	●
VPN Wizard	●	●	●	●
ICSA Firewall		●	●	●
VPNC Certified	●	●	●	●

The NETGEAR ProSafe line of business networking products offers a wide array of easy-to-use, professional-grade switching, wireless, software and security solutions. Backed by a lifetime hardware warranty for the original purchaser, ProSafe products provide an abundance of intelligent, innovative and practical features, addressing the unique requirements of business networks.



System Requirements

- Cable, DSL or wireless broadband modem and
- Internet service
- Ethernet connectivity from broadband modem
- Network card for each connected PC
- Network software (e.g. Windows)
- Internet Explorer® 5.0 or higher or Netscape
- Navigator 4.7 or higher or Firefox® 2.0 or higher

Technical Specifications

• Protocol Support

- Network: IP routing, TCP/IP, UDP, ICMP, PPPoE
- IPV4/IPV6 support
- IP addressing: DHCP (client and server)
- Routing: RIP v1, RIPv2 (static routing, dynamic routing)
- VPN/security: IPsec (ESP), IKE, PKI, HTTPS

• Application Support

- IPsec pass-through, H.323, Instant Messenger™, RealPlayer®, QuickTime®, DialPad, SIP proxy, two-factor authentication

• Functions

- VPN Wizard to simplify configuration of IPsec VPNs
- Auto Detect to automatically detect ISP address type (static, dynamic, PPPoE)
- Port range forwarding
- Port triggering
- Enable/disable WAN ping
- DNS proxy
- MAC address cloning/spoofing
- Network Time Protocol NTP support
- Diagnostic tools (ping, DNS lookup, trace route, other)
- Port/service

• Functions (continued)

- Auto-Uplink on switch ports
- L3 Quality of Service (QoS) LAN-to-WAN and WAN-to-LAN (ToS)
- b/g/n Wireless Interface 2.4Ghz
- SIP ALG
- GUI-selectable DMZ port

• Maintenance

- Save/restore configuration, restore defaults, upgrades via Web browser, display statistics

• Firewall

- Stateful packet inspection (SPI), DoS attack detection/logging, dropped packet log, security event log, email log
- 95 Mbps LAN-WAN Throughput
- 6000 Concurrent Connections

• VPN

- Box-to-box, client-to-box, authentication (MD5, SHA-1), Manual Key, shared secret, key management (IKE, Diffie-Hellman, manual), X.509 certificate support, DES, 3DES and AES IPsec encryption

• Power Adapter

- Plug is localized to country of sale in North America, Australia, Europe, United Kingdom, Japan

• Physical Specifications

- Dimensions (w x d x h): 190 x 125 x 35 mm (7.5 X 4.9 X 1.4 in)
- Weight: 0.59 kg (1.3 lb)

• Hardware

- 300 MHz 32-bit RISC CPU
- 32 MB Flash, 128MB DRAM

• Interface Specifications

- LAN: 10/100/1000 Mbps
- WAN: 10/100/1000 Mbps
- Wireless b/g/n 2.4Ghz

Warranty

- Firewall: NETGEAR Lifetime Warranty
- Power supply: NETGEAR 3-year Warranty

Package Contents

- ProSafe Wireless-N 8-port Gigabit VPN Firewall (FVS318N)
- Ethernet cable
- Power adapter
- Install guide
- Resource CD

ProSupport Maintenance Services

- Optional support packages are available:
- OnCall 24x7 advanced technical support
- XPressHW next business day hardware replacement
- For more information: <http://prosupport.netgear.com>

NETGEAR Related Products

• Software

- ProSafe VPN Client (Trial Version)
- VPNG01L ProSafe VPN Client Professional Software single-user license
- VPNG05L ProSafe VPN Client Professional Software 5-user license

Ordering Information

- North America: FVS318N-100NAS
- Europe: FVS318N-100EUS
- Asia: FVS318N-100AUS

NETGEAR®

350 E. Plumeria Drive
San Jose, CA 95134-1911
1-888-NETGEAR (638-4327)
E-mail: info@NETGEAR.com
www.NETGEAR.com

© 2011 NETGEAR, Inc., NETGEAR, the NETGEAR Logo, and Connect with Innovation are trademarks and/or registered trademarks of NETGEAR, Inc. and/or subsidiaries in the United States and/or other countries. Mac and the Mac logo are trademarks of Apple Inc., registered in the U.S. and other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. All rights reserved.

This product comes with a limited warranty, the acceptance of which is a condition of sale.

*Basic technical support provided for 90 days from date of purchase.