


KT

Grommets, small, single



IP54 IP65

1

Product description

Cable grommets KT small are used with the following cable entry frames:

KEL-U/KEL-ER/KEL (8 - 34) | KVT (38 - 42)

The model range KT small is designed for cable diameters from 2 to 17 mm.

Assembly note

When installing the grommets, the flat side should be facing the middle of the frame. This allows the flat sides of adjacent grommets to match up and provide a secure seal.

Specifications KT grey

Material	Elastomer
Flame class	UL94-Vo, self-extinguishing
IP rating	KT round, single: up to IP65 (in combination with KEL-ER frame) KT special/blank: IP54
NEMA type rating	up to NEMA type 4X (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free

Specifications KT black

Material	Elastomer
Flame class	UL94-HB
IP rating	KT round, single: up to IP65 (in combination with KEL-ER frame) KT special/blank: IP54
NEMA type rating	up to NEMA type 4X (acc. to UL 50E)
Temperature	- 30°C to + 90°C (static)
Properties	Higher chemical resistance

Description	Type	Order No grey	Order No black	Clamping range	PU
BTK	BTK	 41251	 41351	Blank grommet	10
KT round	KT 2	 39934	 41302	2 - 3 mm	10
	KT 3	 41203	 41303	3 - 4 mm	10
	KT 4	 41204	 41304	4 - 5 mm	10
	KT 5	 41205	 41305	5 - 6 mm	10
	KT 6	 41206	 41306	6 - 7 mm	10
	KT 7	 41207	 41307	7 - 8 mm	10
	KT 8	 41208	 41308	8 - 9 mm	10
	KT 9	 41209	 41309	9 - 10 mm	10
	KT 10	 41210	 41310	10 - 11 mm	10
	KT 11	 41211	 41311	11 - 12 mm	10
	KT 12	 41212	 41312	12 - 13 mm	10
	KT 13	 41213	 41313	13 - 14 mm	10
	KT 14	 41214	 41314	14 - 15 mm	10
	KT 15	 41215	 41315	15 - 16 mm	10
	KTs 16	 39901	 39912	16 mm	10
	KTs 17	 39900	 39913	17 mm	10
KT oval	KT oval	 39930	-	approx. 8 × 4 mm	10
KT S1	KT S1	 39931	-		10
KT tele	KT tele	 39929	-	Telephone cable	10
KT tele1	KT tele1	 41257	-	Data cable RJ12	10
KT tele2	KT tele2	 41258	-	Data cable RJ10 / RJ45	10

*Only valid for grey product types

Accessories

KT

Grommets, small, multi



1

Type	Order No grey	Order No black	Clamping range	PU	Description
KT 2 2	39935	39936	2× Ø 2 mm	10	 KT 2 x
KT 2 3	39939	39940	2× Ø 3 mm	10	
KT 2 4	39906	39907	2× Ø 4 mm	10	
KT 2 5	41200	39904	2× Ø 5 mm	10	
KT 2 6	41201	39905	2× Ø 6 mm	10	
KT 2 7	41202	39916	2× Ø 7 mm	10	
KT 2 8	39917	39918	2× Ø 8 mm	10	
KT 4 2	39937	39938	4× Ø 2 mm	10	 KT 4 x
KT 4 3	39914	39915	4× Ø 3 mm	10	
KT 4 4	39909	39911	4× Ø 4 mm	10	
KT 4 5	39908	39910	4× Ø 5 mm	10	
KT 4 6	39932	39933	4× Ø 6 mm	10	
KT-ASI	39902	39903	1 ASI-cable	10	 KT ASI2 I
KT-ASI2 I	39922	39924	2 ASI-cables	10	
KT-ASI2 II	39921	39923	2 ASI-cables	10	
					 KT ASI2 II

Product description

Cable grommets KT small are used with the following cable entry frames:

KEL-U/KEL-ER/KEL (8 - 34) | KVT (38 - 42)

The model range KT small is designed for cable diameters from 2 to 17 mm.

Assembly note

When installing the grommet, the smooth side of the grommet faces the middle of the cable entry frame.

Specifications KT grey

Material	Elastomer
Flame class	UL94-Vo, self-extinguishing
IP rating	KT round, multi: IP54 KT special, multi: IP54
NEMA type rating	NEMA type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free

Specifications KT black

Material	Elastomer
Flame class	UL94-HB
IP rating	KT round, multi: IP54 KT special, multi: IP54
NEMA type rating	NEMA type 12 (acc. to UL 50E)
Temperature	- 30°C to + 90°C (static)
Properties	Higher chemical resistance

Accessories

ST Plugs 49

*Only valid for grey product types