



Filler panel assembly hardware

Application:

For the attachment of filler panels. The length of the collar screw depends on the threaded insert used.

Length 11mm for standard threaded inserts - see page 88.

Length 12.3mm for recessed threaded inserts - see page 88.

Note: Plastic sleeves can be pressed-in by hand. Metal sleeves (for grounding the filler panel) must be pressed-in with a tool, such as a lever press.

Description	Material dimensions	Color/Finish	Order No. 1 kit (100 each)
1 Plastic sleeve	POM	gray	21100-464
		black	21100-591
2 Metal sleeve	Brass	nickel-plated	21100-660
		black	21100-886
	V2A stainless		21100-662
3 Collar screw slotted	Brass (for standard threaded inserts)	nickel-plated	21100-379
		Zn-plated, black	21100-590
	M2.5 x 12.3 (for recessed inserts)	nickel-plated	21100-758
4 Collar screw pozidrive	Steel (for standard threaded inserts)	nickel-plated	21100-748
		black	21100-749
	M2.5 x 12.3 (for recessed inserts)	nickel-plated	21101-101

Gasketing strips

Height	Kit of	Order No. Gasketing kit
3U	10	21101-705
	100	21101-706
6U	10	21101-707
	100	21101-708

1U = 1.75"/44.45mm

1HP = 0.2"/5.08mm