

Rear-mount switches



Base mount switches



■ IP66 handles with screw fixing

Padlockable handles		poles	Ie AC21	Two-screw fixing	Pack	Four-screw fixing 36x36 or 48x48*	Pack	Two-screw fixing	Pack
	Grey plate 67x67mm padlockable, black knob	3	20A	DS0203RRK6	1	DS0203PQK6S	1	DS0203BAK6	1
			32A	DS0323RRK6	1	DS0323PQK6S	1	DS0323BAK6	1
			40A	DS0403RRK6	1	DS0403PQK6S	1	DS0403BAK6	1
		3+N	20A	DS0204RRK6	1	DS0204PQK6S	1	DS0204BAK6	1
			32A	DS0324RRK6	1	DS0324PQK6S	1	DS0324BAK6	1
			40A	DS0404RRK6	1	DS0404PQK6S	1	DS0404BAK6	1
	Yellow plate 67x67mm padlockable, red knob	3	20A	DS0203RRL6	1	DS0203PQL6S	1	DS0203BAL6	1
			32A	DS0323RRL6	1	DS0323PQL6S	1	DS0323BAL6	1
			40A	DS0403RRL6	1	DS0403PQL6S	1	DS0403BAL6	1
		3+N	20A	DS0204RRL6	1	DS0204PQL6S	1	DS0204BAL6	1
			32A	DS0324RRL6	1	DS0324PQL6S	1	DS0324BAL6	1
			40A	DS0404RRL6	1	DS0404PQL6S	1	DS0404BAL6	1
	Grey plate 67x67 mm, black knob padlockable	3	20A	DS0203RQT6L	1	-	-	DS0203BAT6L	1
			32A	DS0323RQT6L	1	-	-	DS0323BAT6L	1
			40A	DS0403RQT6L	1	-	-	DS0403BAT6L	1
		3+N	20A	DS0204RQT6L	1	-	-	DS0204BAT6L	1
			32A	DS0324RQT6L	1	-	-	DS0324BAT6L	1
			40A	DS0404RQT6L	1	-	-	DS0404BAT6L	1
	Yellow plate 67x67 mm, red knob padlockable	3	20A	DS0203RQY6L	1	-	-	DS0203BAY6L	1
			32A	DS0323RQY6L	1	-	-	DS0323BAY6L	1
			40A	DS0403RQY6L	1	-	-	DS0403BAY6L	1
		3+N	20A	DS0204RQY6L	1	-	-	DS0204BAY6L	1
			32A	DS0324RQY6L	1	-	-	DS0324BAY6L	1
			40A	DS0404RQY6L	1	-	-	DS0404BAY6L	1
	Grey plate 48x48 mm, black knob padlockable Only for two-screw fixing	3	20A	DS0203RQT4L	1	-	-	DS0203BAT4L	1
			32A	DS0323RQT4L	1	-	-	DS0323BAT4L	1
			40A	DS0403RQT4L	1	-	-	DS0403BAT4L	1
		3+N	20A	DS0204RQT4L	1	-	-	DS0204BAT4L	1
			32A	DS0324RQT4L	1	-	-	DS0324BAT4L	1
			40A	DS0404RQT4L	1	-	-	DS0404BAT4L	1
	Yellow plate 48x48 mm, red knob padlockable Only for two-screw fixing	3	20A	DS0203RQY4L	1	-	-	DS0203BAY4L	1
			32A	DS0323RQY4L	1	-	-	DS0323BAY4L	1
			40A	DS0403RQY4L	1	-	-	DS0403BAY4L	1
		3+N	20A	DS0204RQY4L	1	-	-	DS0204BAY4L	1
			32A	DS0324RQY4L	1	-	-	DS0324BAY4L	1
			40A	DS0404RQY4L	1	-	-	DS0404BAY4L	1

Two-screw fixing, distance between holes: 28mm (1.10") Vertical or 32mm (1.26") Horizontal

Four-screw fixing, distance between holes: 48x48mm (1.89"x1.89")

* Fixing 48x48 (1.89"x1.89") with adapter flange (included in the package)

 standard article