

Industrial Pumps

3 SERIES

Oil-filled, Direct Drive



Applications

- Submersed or in-line use, water transfer or recirculation, water displays, air conditioning and machine tool coolants

Features

- 1/15 HP oil-filled, heavy-duty motor
- Epoxy-coated cast aluminum housing and cover
- Nylon volute
- Aluminum backplate
- Viton® shaft seal
- Polypropylene screen
- IP 68

Series Specifications

Capacity: 32 LPM @ .31 m
(503038);
38 LPM @ .31 m
(503216)

Shut Off: 5.27 m (503038);
6.4 m (503216)

Discharge: 1/2" MNPT (13 mm)

Intake: 1/2" FNPT (13 mm)

Electrical: 230V, 50Hz, 1.3A, 166W
(503038);
230V, 50/60Hz, 1.7A,
200W (503216)

4 SERIES

Oil-filled, Direct Drive



Applications

- Submersible only, water transfer or recirculation, water displays, air conditioning and machine tool coolants

Features

- 1/12 HP oil-filled motor
- Epoxy-coated cast aluminum housing and cover
- Nylon volute
- Aluminum backplate
- Viton® shaft seal
- IP 68

Series Specifications

Capacity: 41 LPM @ .31 m

Electrical: 230V, 50/60Hz, 1.8A,
210W

Shut Off: 5.6 m

Discharge: 1/2" MNPT (13 mm)

Intake: 3/4" FNPT (19 mm)


Model Characteristics

Item #	Model	Volts	Cord	Weight (Kg.)	Bar	List/Cert.
503038	3E-12N	230	3 m	4	0.53	CE
503216	3E-12NRY	230	3.66 m	3.85	0.64	UR

Model Characteristics

Item #	Model	Volts	Cord	Weight (Kg.)	Bar	List/Cert.
504216	4E-34NRY	230	3.66 m	3.85	0.75	UR

Performance Curves 3E-12N



Performance Curves

