

APPLICANT: Impexron

CERTIFICATE OF INSPECTION

Checked by

Approved by

Model	KH-3065EB-G11	Contact Rating	250VAC, 6A (Resistive Load)	Date	2017. 12. 21
Lot No.	—	Lot Size	- EA	No.	K17 - 08539

Test Items		Description	RESULT
1. Resistance to heat		70 °C ± 2 °C 16 hour	Good
2. Contact Resistance Test.		30mΩ max. (initial value)	2.47
3. Insulation resistance Test.		100MΩ min. at 500 Vdc	Above 100MΩ
4. Dielectric WithStand Voltage		1,500 VAC for a minute	Good
5. Temperature rise Test.		Contact Parts : Below 65°C (Normal temperature)	31
6. Life Test	Mechanically	250,000 Operations (30time/min)	Good
6. Life Test	Electrically	100,000 Operations (30time/min)	Good
7. Strength test of terminal parts		8.2 Kg·cm	Good
8. Vibration		Mechanical durability : 10 to 55Hz 0.75 mm double amplitude.	Good
9. Shock Test		Approx. 20G (200m/s ²)	Good
10.Ambient Temperature Test		-25 ~ + 50 °C (not at freeze)	Good

QA Department
Koino KUN HUNG ELECTRIC CO., LTD