Socket model ES 12

ES12CNER - Pack. 10/220 pcs

Relay socket type ES 12, for undecal relays (11 pins) with 3 PDT and double A2 contact, screw connections, connection facility for input interference suppression modules, for mounting on NS 35/7,5.

Rated current / Rated voltage	12 A / 300 VAC (CSA) 10 A / 300 VAC (UL)
Dielectric strength adjacent contact circuits	2500V
Dielectric strength coil contact circuits	2500V

Connection data	
Conductor cross section solid and stranded	min. 0,5 mm²
Conductor cross section solid and stranded	max. 2,5 mm²
Conductor cross section AWG	min. 20
Conductor cross section AWG	max 14
Stripping length	7 mm
Screw thread	M3

General data	
Width	38 mm
Height	75 mm
Color	Black
Ambient temperature (operation)	-25 °C ... 85 °C





Accessories



Model MH 60

MH60 - Pack. 10/200 pcs

Spring for relay securing

Material: X Cr Ni Steel

Relay height: 58-60 mm

Model MH 55

MH55 - Pack. 10/200 pcs

Spring for relay securing

Material: X Cr Ni Steel

Relay height: 53-55 mm

EVG ELEKTRO-VERTRIEBS-GESELLSCHAFT
MARTENS GMBH & CO KG
TROMPETERALLEE 244-246
41189 MÖNCHENGLADBACH
TEL. 02166 / 5508-0, FAX 02166 / 550890
www.evg.de info@evg.de

standard article

1/1