

Cole-Parmer® Symmetry® EC Toploading Balances

Popular weighing features at an economical cost

- Internal rechargeable battery for portability and convenience
- RS-232 interface allows for communication with a printer
- Print function for GLP compliance
- Capacity tracker warns of approaching overloads
- Security lock-down port

NEW
Expanded

What's included: draft shield, built-in rechargeable battery, and AC power adapter.

Specifications

Calibration: external, with calibration mass

Weighing units: g, lb^t, oz, ct, dr, ozt, gn, N, t, T, H, S, custom

Power: AC adapter or internal rechargeable battery

Capacity	Readability	Repeatability	Linearity	Platform size (dia.)	120 VAC		230 VAC	
					Cat. no.	Price	Cat. no.	Price
100g	0.001 g	±0.002 g	± 0.003 g	4¾" (12.0 cm)	GH-20000-32		GH-20000-33	
200 g	0.01 g	±0.02 g	± 0.02 g	4¾" (12.0 cm)	GH-20000-34		GH-20000-35	
300 g	0.1 g	±0.2 g	± 0.2 g	4¾" (12.0 cm)	GH-20000-48		GH-20000-49	
400 g	0.01 g	±0.02 g	± 0.02 g	4¾" (12.0 cm)	GH-20000-36		GH-20000-37	
500 g	0.1 g	±0.2 g	± 0.2 g	4¾" (12.0 cm)	GH-20000-51		GH-20000-52	
800 g	0.01 g	±0.02 g	± 0.03 g	4¾" (12.0 cm)	GH-20000-38		GH-20000-39	
1200 g	0.1 g	±0.1 g	± 0.2 g	4¾" (12.0 cm)	GH-20000-40		GH-20000-41	
2000 g	0.1 g	±0.2 g	± 0.2 g	5¾" (14.5 cm)	GH-20000-42		GH-20000-43	
4000 g	0.1 g	±0.2 g	± 0.2 g	5¾" (14.5 cm)	GH-20000-44		GH-20000-45	
6000 g	1 g	±1 g	± 2 g	5¾" (14.5 cm)	GH-20000-46		GH-20000-47	

[†]lb not available on 100 g models



Symmetry®

Accessories

- [GH-10000-38](#) Compact thermal printer
- [GH-10000-47](#) Kensington™-type security lock and cable
- [GH-17101-52](#) NIST-traceable calibration with data for balances

A&D GX/GF Toploading Balances

No waiting—fast, one-second response time

- Store weighing data—GX series stores 200 sets and the GF series stores 20 sets
- Complementary WinCT software supports data collection and statistical analysis
- Internal calibration models (GX series) have automatic calibration
- Connect to peripheral devices with RS-232 output

What's included: software, underhook, draft shield (models 11133-00 and -02 only), and 110 VAC adapter with 6-ft (1.8-m) cord.

Specifications

Calibration: internal (GX) or external (GF)

Weighing units: g, oz, ozt, lb, lb:oz, ct, dwt, gn, tael, tola, momme, mesghal, custom

Power: 120/220 VAC

Capacity	Readability	Repeatability	Linearity	Pan size (L x W)	Catalog number	Price
Balances with external calibration (GF series)						
210 g 310 g	0.001 g	±0.001 g	±0.002 g	5" x 5" (12.7 x 12.7 cm)	GH-11133-00	
410 g 610 g	0.001 g	±0.001 g	±0.003 g		GH-11133-02	
810 g 1100 g					GH-11110-61	
					GH-11110-62	
1210 g 2100 g 3100 g	0.01 g	±0.01 g	±0.02 g	6½" x 6½" (16.5 x 16.5 cm)	GH-11133-06	
4100 g 6100 g	0.01 g	±0.01 g	±0.02 g		GH-11133-08	
			±0.03 g		GH-11133-10	
6100 g	0.1 g	±0.1 g	±0.1 g		GH-11110-65	
					GH-11110-66	
					GH-11133-12	
Balances with internal calibration (GX series)						
210 g 410 g	0.001 g	±0.001 g	±0.002 g	5" x 5" (12.7 x 12.7 cm)	GH-11118-00	
810 g 1100 g			±0.003 g		GH-11118-02	
					GH-11110-58	
2100 g 4100 g 6100 g	0.01 g	±0.01 g	±0.02 g ±0.02 g ±0.03 g	6½" x 6½" (16.5 x 16.5 cm)	GH-11118-06	
6100 g			±0.03 g		GH-11118-08	
6100 g 8100 g	0.1 g	±0.1 g	±0.1 g		GH-11118-12	
					GH-11118-10	
					GH-11118-14	



Accessories

- [GH-01038-65](#) Adapter, 220 VAC
- [GH-11110-47](#) External data logger
- [GH-17101-52](#) NIST-traceable calibration with data for balances

Wait!

**There's More at
ColeParmer.com**

- ✓ Search 100,000+ products
- ✓ Find full product details
- And much more!