

Coaxial

Voltage Controlled Oscillator

ZX95-2500W+

Wide Band 1000 to 2400 MHz

Features

- very wide band frequency range
- low phase noise
- low pushing
- low pulling
- protected by US patent 6,790,049

Applications

- r & d
- lab
- instrumentation
- wireless communications
- military & avionics



CASE STYLE: GB956

Connectors	Model
SMA	ZX95-2500W-S+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies,kHz Typ.				TUNING					NON HARMONIC SPURIOUS (dBc)	HARMONICS (dBc)		PULLING pk-pk @12 dB (MHz)	PUSHING (MHz/V)	DC OPERATING POWER Vcc Current (volts) (mA)	
								VOLTAGE RANGE (V)	SENSI- TIVITY (MHz/V)	PORT CAP (pF)	3 dB MODULATION BANDWIDTH (MHz)								
	Min.	Max.	Typ.	1	10	100	1000	Min.	Max.	Typ.	Typ.	Typ.	Typ.	Typ.	Max.	Typ.	Typ.	Max.	
ZX95-2500W+	1000	2400	+3.5	-65	-93	-116	-138	0.5	25	40-96	65	20	-90	-13	-	0.3	4.5	5	48

Maximum Ratings


Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	6V
Absolute Max. Tuning Voltage (Vtune)	27V
All specifications	50 ohm system

Permanent damage may occur if any of these limits are exceeded.



NOTE: When soldering the DC connections, caution must be used to avoid overheating the DC terminals. See Application Note [AN-40-10](#).

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
1.20	.75	.46	1.18	.04	.38	.38	.57	.18	.33	.21	.22	.18	1.00	.50	.35	.18	.106	grams
30.48	19.05	11.68	29.97	1.02	9.65	9.65	14.48	4.57	8.38	5.33	5.59	4.57	25.40	12.70	8.89	4.57	2.69	35.0

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com







REV. A
M152326
EDR-9410F2
ZX95-2500W+
RAV
150923
Page 1 of 2

Performance Data & Curves*

ZX95-2500W+

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			Icc (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (KHz)	PHASE NOISE at 1700 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	116.32	875.2	867.1	859.1	2.80	1.87	1.01	36.86	-10.9	-22.2	-27.2	0.41	0.01	-68.3	-92.5	-113.6	-133.9	1.0	-62.76
0.50	104.94	933.6	925.3	917.9	2.88	2.03	1.39	37.15	-10.7	-21.6	-26.8	0.33	0.05	-68.8	-93.2	-114.5	-134.9	2.0	-70.70
2.00	86.83	1087.6	1077.0	1069.6	2.99	2.35	2.11	38.04	-11.1	-21.5	-25.3	0.42	0.03	-70.6	-94.8	-116.4	-137.2	3.5	-76.91
3.00	85.89	1175.9	1163.8	1155.9	3.10	2.51	2.39	38.72	-11.6	-22.5	-25.1	0.76	0.05	-71.0	-95.3	-117.3	-138.3	6.0	-82.81
4.00	88.33	1262.4	1249.7	1241.4	3.36	2.76	2.71	39.45	-10.9	-22.2	-25.3	1.00	0.06	-69.4	-95.4	-117.7	-139.1	8.5	-87.06
6.00	93.94	1443.8	1430.6	1421.7	4.12	3.85	3.82	40.74	-9.9	-20.2	-35.4	1.60	0.20	-67.9	-93.3	-116.4	-139.6	10.0	-88.78
8.00	92.86	1629.0	1617.9	1610.6	4.07	4.27	4.48	40.71	-9.9	-17.6	-32.4	4.86	0.30	-64.8	-89.0	-112.1	-135.4	20.8	-96.83
9.00	93.77	1723.5	1710.8	1703.5	4.08	4.24	4.59	39.97	-10.2	-17.2	-28.0	6.37	0.48	-61.9	-88.5	-112.4	-135.4	35.5	-102.35
10.00	93.03	1818.4	1804.5	1796.4	4.10	4.18	4.61	39.15	-10.9	-17.8	-32.9	7.11	0.30	-62.9	-88.4	-112.4	-135.3	60.7	-107.58
12.00	87.05	2005.2	1989.1	1979.3	4.00	4.11	4.48	37.88	-11.2	-22.5	-31.6	7.86	0.26	-63.2	-90.1	-114.2	-136.9	85.2	-111.02
13.00	81.25	2092.8	2076.1	2066.4	3.98	3.89	4.36	37.46	-12.4	-29.0	-38.9	7.43	0.24	-64.6	-91.9	-115.7	-138.1	100.0	-112.55
14.00	74.68	2174.1	2157.4	2147.5	3.77	3.66	4.03	37.17	-13.8	-29.6	-56.5	6.56	0.36	-64.3	-93.6	-117.2	-139.2	142.9	-115.93
15.00	68.14	2248.8	2232.1	2222.6	3.47	3.39	3.79	36.95	-14.7	-23.4	-46.5	5.47	0.46	-63.5	-93.9	-117.8	-139.6	167.8	-117.46
16.00	61.56	2316.9	2300.2	2291.2	3.15	3.06	3.24	36.79	-14.9	-22.1	-42.8	4.16	0.53	-67.4	-94.8	-118.5	-140.2	200.6	-119.22
18.00	49.83	2433.6	2416.7	2408.2	2.16	2.04	2.18	36.61	-17.5	-26.2	-34.1	2.58	0.37	-66.9	-93.7	-118.5	-140.3	281.6	-122.55
19.00	41.20	2481.8	2466.5	2457.6	1.71	1.14	1.32	36.56	-16.3	-27.4	-33.7	2.16	0.49	-66.3	-94.2	-119.0	-140.4	330.7	-124.15
20.00	36.89	2523.7	2507.7	2499.4	1.40	0.99	1.04	36.49	-16.6	-29.5	-34.9	1.79	0.46	-67.7	-94.6	-119.0	-140.2	464.2	-127.63
22.00	24.62	2590.5	2573.1	2565.2	0.31	-0.07	-0.06	36.42	-18.3	-32.4	-31.7	0.88	0.41	-68.7	-95.5	-119.0	-140.1	554.9	-129.50
24.00	14.85	2632.6	2617.0	2609.2	-0.47	-1.02	-1.06	36.37	-19.9	-32.8	-30.2	0.47	0.38	-68.9	-95.9	-119.3	-140.4	914.6	-134.69
25.00	12.50	2648.6	2631.9	2624.3	-0.95	-1.39	-1.53	36.33	-18.8	-31.4	-29.5	1.06	0.34	-67.3	-95.7	-118.9	-139.9	1000.0	-135.63

*at 25°C unless mentioned otherwise



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Voltage Controlled Oscillator

ZX95-2500W+






Typical Performance Data

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ OFFSET (KHz)	PHASE NOISE (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C	F2	F3	F4			
0.00	116.32	875.2	867.1	859.1	2.80	1.87	1.01	-10.85	-22.18	-27.16	0.41	1	-63
0.50	104.94	933.6	925.3	917.9	2.88	2.03	1.39	-10.68	-21.60	-26.75	0.33	10	-89
2.00	86.83	1087.6	1077.0	1069.6	2.99	2.35	2.11	-11.14	-21.48	-25.31	0.42	100	-113
3.00	85.89	1175.9	1163.8	1155.9	3.10	2.51	2.39	-11.56	-22.46	-25.06	0.76	1000	-136
4.00	88.33	1262.4	1249.7	1241.4	3.36	2.76	2.71	-10.93	-22.20	-25.28	1.00		
5.00	92.56	1351.4	1338.1	1329.4	3.78	3.33	3.23	-10.50	-21.77	-28.80	1.23		
6.00	93.94	1443.8	1430.6	1421.7	4.12	3.85	3.82	-9.92	-20.23	-35.37	1.60		
7.00	93.33	1536.4	1524.6	1516.3	4.22	4.12	4.20	-9.94	-18.20	-37.31	2.92		
8.00	92.86	1629.0	1617.9	1610.6	4.07	4.27	4.48	-9.89	-17.59	-32.36	4.86		
9.00	93.77	1723.5	1710.8	1703.5	4.08	4.24	4.59	-10.22	-17.15	-28.02	6.37		
10.00	93.03	1818.4	1804.5	1796.4	4.10	4.18	4.61	-10.92	-17.82	-32.86	7.11		
11.00	91.54	1912.6	1897.6	1888.6	4.03	4.20	4.67	-10.55	-19.05	-31.96	7.47		
12.00	87.05	2005.2	1989.1	1979.3	4.00	4.11	4.48	-11.19	-22.45	-31.61	7.86		
13.00	81.25	2092.8	2076.1	2066.4	3.98	3.89	4.36	-12.43	-29.01	-38.92	7.43		
14.00	74.68	2174.1	2157.4	2147.5	3.77	3.66	4.03	-13.78	-29.59	-56.46	6.56		
15.00	68.14	2248.8	2232.1	2222.6	3.47	3.39	3.79	-14.69	-23.39	-46.53	5.47		
16.00	61.56	2316.9	2300.2	2291.2	3.15	3.06	3.24	-14.94	-22.08	-42.76	4.16		
17.00	54.89	2378.4	2361.8	2352.9	2.61	2.31	2.57	-16.51	-24.20	-36.54	3.34		
18.00	49.83	2433.6	2416.7	2408.2	2.16	2.04	2.18	-17.46	-26.23	-34.14	2.58		
19.00	41.19	2481.8	2466.5	2457.6	1.71	1.14	1.32	-16.28	-27.36	-33.74	2.16		
20.00	36.89	2523.7	2507.7	2499.4	1.40	0.99	1.04	-16.64	-29.51	-34.87	1.79		
21.00	28.52	2559.6	2544.6	2536.4	0.90	0.19	0.32	-17.72	-27.43	-32.44	1.41		
22.00	24.62	2590.5	2573.1	2565.2	0.31	-0.07	-0.06	-18.34	-32.41	-31.69	0.88		
23.50	17.08	2622.9	2607.4	2599.4	-0.18	-0.77	-0.81	-18.73	-33.26	-30.29	0.15		
24.00	14.85	2632.6	2617.0	2609.2	-0.47	-1.02	-1.06	-19.92	-32.81	-30.18	0.47		
25.00	12.50	2648.6	2631.9	2624.3	-0.95	-1.39	-1.53	-18.78	-31.35	-29.45	1.06		
26.00	10.42	2661.1	2644.4	2636.5	-1.33	-1.80	-1.89	-18.97	-35.35	-32.53	1.43		
27.00	10.42	2671.0	2654.8	2646.8	-1.56	-2.16	-2.26	-20.04	-33.43	-30.78	1.59		


Voltage Controlled Oscillator

ZX95-2500W+

Typical Performance Data



Outline Dimensions



CASE #.	A	B	C	D	E	F	G	H	J	K	L	M	N
GB956	1.20 (30.48)	.75 (19.05)	.46 (11.68)	1.18 (29.97)	.04 (1.02)	.38 (9.65)	.38 (9.65)	.57 (14.48)	.18 (4.57)	.33 (8.38)	.21 (5.33)	.22 (5.59)	.18 (4.57)

CASE #.	P	Q	R	S	T	WT, GRAM
GB956	1.00 (25.40)	.50 (12.70)	.35 (8.89)	.18 (4.57)	.106 (2.69)	35.0

Dimensions are in inches (mm). Tolerances: 2Pl. $\pm .03$; 3Pl. $\pm .015$

Notes:

- Case material: Brass.
- Case finish: Nickel plate.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I