

# Conventional Intrinsically Safe Mounting Base **YBN-R/4(IS)**



## Features

- ▶ Low Profile, only 8 mm
- ▶ Rugged design
- ▶ Dedicated cable screen terminal
- ▶ Accepts from 1 to 2.5 mm<sup>2</sup> cables
- ▶ Quick connection via square cable clamps
- ▶ Electronics free

## Description

Model YBN-R/4(IS) is a Conventional Detector Mounting Base associated with the CDX Range of Intrinsically Safe Detectors and is fully compatible with the majority of existing conventional fire alarm control panels.

It is supplied with square cable clamps for secure and reliable cable termination but the base does not provide line continuity during detector removal, therefore if Call Points are being used then these should be wired onto the zone first.

## Specification

|  |                                   |
|--|-----------------------------------|
| Ordering Code                            | YBN-R/4(IS)                       |
| Maximum Humidity                         | 95%RH - Non Condensing (at 40 °C) |
| Colour / Material                        | Ivory White / ABS                 |
| Weight (g) / Diameter (mm) / Height (mm) | 51 / 100 / 8                      |
| Fixing Centres (mm)                      | 48 ~ 74                           |
| Maximum Wire Thickness                   | 2.5 mm <sup>2</sup> Cables        |