

Date: 19.02.2015

Contact Block: ATL

General Data

Type Reference:	ATL
Description:	Illuminated contact block, positive opening contact
Approvals:	CCC, CSA, ENEC10, VDE, CE, GOST-R, NV, UR, Zwangsöffnung
Nature of contact:	1NC + 1NO
Protection class:	II (protective insulation)
Operation travel:	6 mm
Connection type:	Faston terminals 2 x 2.8mm x 0.8 mm
Contact material:	AgNi
Max. storage temperature:	-50°C ... 85°C
Max. operating temperature:	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LED's
Mechanical life:	1m operations
Electrical life (rated load):	1m operations
Contact resistance NO:	< 20 mOhm (new state)
Contact resistance NC:	< 20 mOhm (new state)
Min. current:	1 mA (under laboratory conditions)
Min. voltage:	5 V
Bouncing time NO:	< 10ms
Bouncing time NC:	< 20ms
Positive opening contact:	acc. to EN60947-5-1, appendix. K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category:	AC15 A300	DC13 Q300
Rated insulation voltage U_i :	250 V	300 V
Rated operating voltage U_e :	250V	250V / 125V / 60V / 24V
Rated operating current I_e :	3A	0.2A / 0.4A / 1A / 2A
Breaking capacity:	10Ie	1.1Ie
Continuous thermal current:	6 A	

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage U_e :	250 V~
Rated current I_e :	6(3) A

Technical Data - Lamp

Lamp socket:	T5,5K
Max. lamp voltage:	60V
Max. lamp output:	1.2W
Definition:	X1...anode, X2...cathode

Note


Notice for emergency-stop contact blocks:

For inverters of the Za type (as defined in EN 60947-5-1), only the NC contact must be used for remotely controlled safety circuits.


Photo



Dimensional drawing



Operating travel diagram



- subject to alterations -