# LARGE BORE VALVE SYSTEMS

STRAIGHT VAIVES AND EXTENSIONS

### STRAIGHT VALVES

#### H-41

Tubeless spud, used with all targe Bore swivel valves, Fits 13/16" rim hole.

### H-42

Straight valve, equipped with core and hex cap.

### H-45

Spud and valve complete. Consists of H-41 & H-42.

### STRAIGHT VALVES

HALTEC NO.	TR NO.	HEIGHT	
		INCHES	MM
H-410 (5) (5) (6)	SP-2	11/16	15,8 (1996)
H-42	TRJ-670-2	1 1/2	38.1

### TECH TIP

THE ULTIMATE FLOW RESTRICTION IN ANY INFLATION/DEFLATION SERVICE IS THE DIAMETER OF THE VALVE AND/OR VALVE CORE.



H-41





14-45

### HAND-BENDABLE EXTENSIONS

1				
HALTEC NO.	EFFECTIVE LENGTH			
	INCHES	WW		
-7535-3 1/2 Hill Hill Hill Hill Hill	3 1/2	89.6		
753S-4	4	101.6		
753541/2	4 1/2	114.3		
753S-8	8	203.2		
7538-9	9 (1) 10 (1) (1) (1)	228.6		
753S-10	10	254		
763\$-11 1/2	111/2	292.1		
<b>763</b> S-12	12	304.8		
7638-13 1/2	13 1/2	342.9		
753S-16	16	406.4		
763\$-17	17	4318		
7535-17 1/2	17 1/2	444.5		
753S-16	16	457.2		
7535-18 1/2	18 1/2	469.9		
7635-19	10	482.6		
753S-20 1/2	20 1/2	520.7		
7538-21	21	533.4 (1) (1) (1) (1) (1) (1)		
763S-21 1/2	21 1/2	546.1		
7535-22 1/2	221/2	571.5		
753S-23	23	584.2		
7535-23 1/2	23.122	596.9		
7635-24 1/2	24 1/2	622.3		
7538-25	26% (1) (5) (6) (6) (6)	635.3		
753\$-29 1/2	29 1/2	749.3		
7535-32	32	8128		

#### TECH TIP

THE 3/4" HEX SEALING NUT, 463, IS INCLUDED WITH EACH EXTENSION. THE NUT COMES WITH A WASHER THAT FORMS A TIGHT SEAL BETWEEN THE EXTENSION AND THE VALVE. IT ALSO ACTS AS A LOCK, TO KEEP THE EXTENSION FROM COMING LOOSE. FOR SHIPPING PURPOSES, THE 463 SEALING NUT IS SCREWED ONTO THE EXTENSION, BUT WHEN IN USE MUST BE MOVED TO THE VALVE BEFORE INSTALLING THE EXTENSION.

## **EXTENSIONS**

### HAND-BENDABLE

Equipped with 2 lock nots and 3/4" hex sealing not. A tellar gasket seals on end of valve, the lead seal in the sealing not is forced into the threads for a second seal, positively locking extension to valve. Cap and core not included. They should be removed from valve and transferred to extension. Should be anchored to rim.

Other lengths can be ordered.



7535- LENGTH

