

CBD Series

with UL94V-0 polyamide insulating body

- UL94V-0
- universal mounting onto both PR/DIN and PR/3 type rails - according to IEC 60715 Std., "G32" and "TH/35" types
- **CESI 01 ATEX 090 U** Ex e certificate
I M2 / II 2 G D operating temperature range:
-40 ÷ +80 °C
- **CoC IEC Ex CES 09.0009U** Ex e II
- when rail assemblies are to be manufactured for potentially explosive environments (Ex e) please refer to the instructions given on page A14
- available in standard (beige RAL 1001 colour) or (Ex) i "intrinsic safety" circuits (blue RAL 5015 colour) versions



(**): 25 A factory wiring only

(**): 32 A factory wiring only

(***) if shielded cables are to be connected, when using CB/SH screening lug, the rated voltage is reduced to 200 V

beige version	
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm²)
connecting capacity	
flexible	(mm²)
rigid	(mm²)
max. flexible with ferrule (mm²)-ferrule type	
rated voltage / rated current / gauge conf. to IEC 60947-7-1	
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage /	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

APPROVALS

ACCESSORIES	
End sections	beige blue
Permanent cross connection	
Rated current carrying capacity of jumper (same, Ex e version)	(A)
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve (same, Ex e version)	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Modular test plug	
End section for modular test plug	
Numbering strip	
Warning plate	on adjacent terminal blocks
Cover for cross-connection	
Marking tag	printed or blank
End bracket	
Mounting rail according to IEC 60715 Std.	
Screening lug	

CBD.2	
Cat. No.	CB110
CBD.2 (Ex)i	
Cat. No.	CBX12
feed-through	
2,5	
0,5 ÷ 4	
0,5 ÷ 4	
2,5 - WP25/14	
800 V / 24 A / A3	
600 V / 20 A (*) / 20-12 AWG / 5,5 lb.in	
500 V / 630 V	
8 KV / 3	
13	
0,4 / 0,8	
47 / 40,5 / 5,5	
55 / 40,5 / 5,5	
51 / 40,5 / 5,5	
IEC Ex pending	

CBD.4	
Cat. No.	CB240
CBD.4 (Ex)i	
Cat. No.	CBX24
feed-through	
4	
0,5 ÷ 6	
0,5 ÷ 6	
4 - WP40/16	
800 V / 32 A / A4	
600 V / 30 A (**) / 20-10 AWG / 8,9 lb.in	
500 V / 630 V	
8 KV / 3	
14	
0,5 / 1,2	
52 / 44 / 6,5	
60 / 44 / 6,5	
56 / 44 / 6,5	
IEC Ex pending	

CBD.6	
Cat. No.	CB340
CBD.6 (Ex)i	
Cat. No.	CBX34
feed-through	
6	
0,5 ÷ 10	
0,5 ÷ 10	
6 - WP60/20	
800 V / 41 A / A5	
600 V / 50 A / 20-8 AWG / 13,3 lb.in	
500 V / 630 V	
8 KV / 3	
14	
0,8 / 1,4	
52 / 44 / 8	
60 / 44 / 8	
56 / 44 / 8	
IEC Ex pending	

Type	Cat. No.
CB2/PT	CB111
CB2/PT (Ex)i	CBX13
PM/20/2 poles (pre-assembled)	PM202
PM/20/3 poles (pre-assembled)	PM203
PM/20/5 poles (pre-assembled)	PM205
PM/20/10 poles (pre-assembled)	PM210
24 / (24)	
POS/11	POS11
PMP/01	PMP01
CPM/21 (CPX/21)	CPM21 (CPX21)
DFU/1	DU01..
DFM/600	DF600
PSD/D	PD004
SDD/1	DD001
SDD/5	DD005
SD5/PT	DD501
-	
TQM/02 su 4	TQM02
-	
PRP/6	PRP06
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
CBD/SH (*)	CB009

Type	Cat. No.
CB4/6/PT	CB241
CB4/6/PT (Ex)i	CBX25
PM/40/2 poles (pre-assembled)	PM402
PM/40/3 poles (pre-assembled)	PM403
PM/40/5 poles (pre-assembled)	PM405
PM/40/10 poles (pre-assembled)	PM400
32 / (32)	
POS/42	POS42
PMP/42	PMP42
CPM/12 (CPX/12)	CPM12 (CPX12)
DFU/4	DU04..
DFM/600	DF600
PSD/A	PD001
SDD/1	DD001
SDD/6	DD006
SD6/PT	DD601
-	
TQM/12 su 3 e su 4	TTM12
-	
PRP/6	PRP06
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
CBD/SH (*)	CB009

Type	Cat. No.
CB4/6/PT	CB241
CB4/6/PT (Ex)i	CBX25
PM/60/2 poles (pre-assembled)	PM602
PM/60/3 poles (pre-assembled)	PM603
PM/60/5 poles (pre-assembled)	PM605
PM/60/10 poles (pre-assembled)	PM610
41 / (41)	
POS/93	POS93
PMP/13	PMP13
CPM/83 (CPX/83)	CPM83 (CPX83)
DFU/4	DU04..
DFM/600	DF600
PSD/N	PD013
SDD/1	DD001
-	
-	
TTM/15 su 3	TTM15
TQM/15 su 4	TQM15
PRP/7	PRP07
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
CBD/SH (*)	CB009