

### ProTowWash® – Transport Trailer with 270 Gallon Tank

The T300 tandem axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The 270 Gallon water tank provides ample water to sustain many remote-cleaning requirements. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service—engineered into the T300 Series Pro Tow Wash

TECHNICAL DATA	T300N	T300EE	T300S
MACHINE CAPACITY	To be ordered with a hot water skid (up to 1100# total)		
SUSPENSION / AXLE	Two 3700# Torsion Axles—Up to 300% more wheel travel over conventional trailers		
TRAILER BRAKES	None	Electric Brake, both axles***	Surge Brakes
WHEEL / TIRE	4 - 13" Spoke Rims, 5 Lug / ST175/80D/13 Tires, 1100 Pounds capacity per tire		
COUPLER / TONGUE	2" Ball Coupler, Dual 3/8" Safety Chains		
VEHICLE HITCH / GVWR	2" Ball Hitch, Class IV 6000 Pound Rated, 20" to top of ball when trailer is attached 4400# GVWR – requires 2", class III ball on tow vehicle		
FENDERS	12 GA steel fender with recessed tail light mount and license plate light		
LIGHTS	Recessed Rubber Grommet Snap-In, DOT Approved		
WIRING	4 way flat connector	7 way molded connector	4 way flat connector
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter		
WATER TANK	270 Gallon total Capacity, Seamless Polyethylene, 10" lid; Garden Hose Fill Fitting		
TANK DRAW / FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve		
CHASSIS CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish		
WEIGHT/DIMENSIONS	761# (w/o machine)	893# (w/o machine)	775# (w/o machine)
	130" Long x 68" Wide x 61" High		

Note: Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped to distributors only, not available to drop ship – Assembly Required

\*\*\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery. Fenders and tires require installation if being shipped.

#### Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

#### Options...

Hose Reels, Lunette eye hitch, Custom trailer color (CTRLR), Front Bucket Rack (ACR02), 3-way ball valve (AW006), Light Bar rack (HLB98), High water tank shutoff (VVF18), Low water shutdown (AW410)-installed, Sand hopper, Hydro Vacuum wastewater recycle (AZV), 12v Chemical sprayer with 40gal tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included  
 Shown with optional Hose Reel and Light Bar

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

**\*WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.