

ROULEMENTS A ROULEAUX CONIQUES

▲ Illustration technique page 97

Tableau dimensionnel

d ₁	d ₂	l ₁	Mod.	Référence	Schéma	Ligne	Charge (kN)		Vitesse (min ⁻¹)	
							dyn. C	stat. Co	graisse	huile
30	72	20,8	L5- 30306M	L5-01	25	25	56,1	56	5600	7500
	72	28,75	L5- 32306	L5-01	26	26	76,5	85	5300	7000
31,75	59,13	16,76	L5- LM67048/010	L5-01	27	27	33,5	39,4	6300	8500
35	62	18	L5- 32007X	L5-01	28	28	42,9	54	6000	8000
	72	18,25	L5- 30207M	L5-01	29	29	51,2	56	5300	7000
	72	24,3	L5- 32207M	L5-01	30	30	66	78	5300	7000
	72	28	L5- 33207	L5-01	31	31	84,2	106	4800	6300
	80	22,75	L5- 31307	L5-01	32	32	61,6	67	4500	6000
	80	22,8	L5- 30307M	L5-01	33	33	72,1	73,5	5000	6700
	80	32,75	L5- 32307	L5-01	34	34	95,2	106	4800	6300
40	68	19	L5- 32008XM	L5-01	35	35	52,8	71	5300	7000
	75	26	L5- 33108	L5-01	36	36	79,2	104	5000	6700
	80	19,75	L5- 30208M	L5-01	37	37	61,6	68	4800	6300
	80	24,8	L5- 32208M	L5-01	38	38	74,8	86,5	4800	6300
	80	32	L5- 33208/Q	L5-01	39	39	105	132	4300	5600
	80	32,75	L5- 32308	L5-01	40	40	117	140	4000	5300
	90	25,25	L5- 31308	L5-01	41	41	73,7	81,5	4000	5300
	90	25,3	L5- 30308M	L5-01	42	42	85,8	95	4500	6000
41,28	73,43	19,81	L5- LM501349/310	L5-01	43	43	55,4	68,8	4800	6300
45	75	20	L5- 32009XM	L5-01	44	44	58,3	80	4800	6300
	80	26	L5- 33109/Q	L5-01	45	45	84,2	114	4500	6000
	85	20,75	L5- 30209M	L5-01	46	46	66	76,5	4500	6000
	85	24,8	L5- 32209M	L5-01	47	47	80,9	98	4500	6000
	85	32	L5- 33209	L5-01	48	48	108	143	4000	5300
	90	35,25	L5- 32309M	L5-01	49	49	140	170	3600	4800
	100	27,3	L5- 30309M	L5-01	50	50	108	120	4000	5300

Mod. Référence

EXEMPLE DE COMMANDE L5- 32007X

d ₁	d ₂	l ₁	Mod.	Référence	Schéma	Ligne	Charge (kN)		Vitesse (min ⁻¹)	
							dyn. C	stat. Co	graisse	huile
45	100	27,3	L5- 31309M	L5-01	51	51	91,3	102	3400	4500
50	80	20	L5- 32010X	L5-01	52	52	60,5	88	4500	6000
	80	24	L5- 33010/Q	L5-01	53	53	69,3	102	4500	6000
	90	21,75	L5- 30210M	L5-01	54	54	76,5	91,5	4300	5600
	90	24,8	L5- 32210M	L5-01	55	55	82,5	100	4300	5600
	90	32	L5- 33210/Q	L5-01	56	56	114	160	3800	5000
	110	29,25	L5- 30310	L5-01	57	57	125	140	3600	4800
	110	29,25	L5- 31310M	L5-01	58	58	106	120	3200	4300
	110	42,25	L5- 32310	L5-01	59	59	172	212	3200	4300
55	90	23	L5- 32011XM	L5-01	60	60	80,9	116	4000	5300
	95	30	L5- 33111/Q	L5-01	61	61	110	156	3800	5000
	100	22,75	L5- 30211M	L5-01	62	62	89,7	106	3800	5000
	100	26,8	L5- 32211M	L5-01	63	63	106	129	3800	5000
	100	35	L5- 33211/Q	L5-01	64	64	110	156	3800	5000
	120	31,5	L5- 30311	L5-01	65	65	142	163	3200	4300
	120	31,5	L5- 31311M	L5-01	66	66	121	137	2800	3800
60	95	23	L5- 32012X	L5-01	67	67	82,5	122	3800	5000
	95	27	L5- 33012	L5-01	68	68	91,3	143	3800	5000
	100	30	L5- 33112/Q	L5-01	69	69	117	170	3600	4800
	110	23,75	L5- 30212M	L5-01	70	70	99	114	3400	4500
	110	29,8	L5- 32212	L5-01	71	71	125	160	3400	4500
	110	38	L5- 33212	L5-01	72	72	168	236	3000	4000
	130	33,5	L5- 30312	L5-01	73	73	168	196	3000	4000
	130	33,5	L5- 31312M	L5-01	74	74	145	166	2600	3600
	130	48,5	L5- 32312	L5-01	75	75	229	290	2600	3600
65	100	23	L5- 32013X	L5-01	76	76	84,2	127	3400	4500