

Safety transformers 42V



Technical data

Width x height x depth: Series 6200: 280 x 276 x 180 mm ⁽²⁾
 Series 6700: 350 x 311 x 247 mm ⁽³⁾
 Series 3500: 360 x 250 x 360 mm ⁽⁴⁾
 Series 4300: 490 x 160 x 350 mm ⁽⁵⁾
 Series 3900: 250 x 360 x 173 mm ⁽⁶⁾

Type of protection: IP44 (IP65 on request)

Material: Cover: solid rubber halogen-free
 Cover Series 4300: Plastic
 Cabinet: solid rubber halogen-free

Gasket: Foamed polyurethane gasket

Equipment examples portable safety transformers 42V

EDP No.	Product ID No.	Voltage max. amp.	Weight in kg	Entry	Equipment	
47594	62032044.ETA ⁽²⁾	320 VA 6 A	9	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	2/CEE 2x16A 42V	
47080	62050044.ETA ⁽²⁾	500 VA 10 A	11.5	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	2/CEE 2x16A 42V	
47596	620500444.ETA ⁽²⁾	500 VA 10 A	11.7	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	3/CEE 2x16A 42V	
47231	67010004444.ETA ⁽³⁾	1000 VA 2 x 10 A	18	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	4/CEE 2x16A 42V	
47939	35015004444.ETA ⁽⁴⁾	1500 VA 2 x 15 A	19	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	4/CEE 2x16A 42V	
46446	43020004444.ETA ⁽⁵⁾	2000 VA 4 x 10 A	30	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	4/CEE 2x16A 42V	
47937	4302500444.ETA ⁽⁵⁾	2500 VA 3 x 15 A	32.5	3 m connection cable 2x1.5 mm ² with contour plug 16A 230V	3/CEE 2x16A 42V	

Equipment examples safety transformers 42V for wall mounting

EDP No.	Product ID No.	Voltage max. amp.	Weight in kg	Entry	Equipment	
48121	39032044.ETA.1M20 ⁽⁶⁾	320 VA 6 A	12.5	1/M20	2/CEE 2x16A 42V	
47938	39050044.ETA.1M20 ⁽⁶⁾	500 VA 10 A	15	1/M20	2/CEE 2x16A 42V	

Design the optimum solution for your requirements with our engineers.
 Engraving possible.