

DC-Micromotors

Precious Metal Commutation

6,8 mNm

8,5 W

Series 2224 ... SR

Values at 22°C and nominal voltage		2224 U	003 SR	006 SR	012 SR	018 SR	024 SR	036 SR		
1	Nominal voltage	U_N	3	6	12	18	24	36	V	
2	Terminal resistance	R	0,56	1,94	8,71	17,5	36,3	91,4	Ω	
3	Output power	$P_{2nom.}$	3,92	4,55	4,05	4,54	3,88	3,46	W	
4	Efficiency, max.	$\eta_{max.}$	80	82	82	82	81	80	%	
5	No-load speed	n_0	8 100	8 200	7 800	8 100	7 800	7 800	min ⁻¹	
6	No-load current, typ. (with shaft ø 2 mm)	I_0	0,066	0,029	0,014	0,01	0,007	0,005	A	
7	Stall torque	M_H	18,5	21,2	19,8	21,4	19	16,9	mNm	
8	Friction torque	M_R	0,23	0,2	0,2	0,21	0,2	0,22	mNm	
9	Speed constant	k_n	2 730	1 380	657	454	328	219	min ⁻¹ /V	
10	Back-EMF constant	k_E	0,366	0,725	1,52	2,2	3,04	4,56	mV/min ⁻¹	
11	Torque constant	k_M	3,49	6,92	14,5	21	29,1	43,5	mNm/A	
12	Current constant	k_I	0,286	0,144	0,069	0,048	0,034	0,023	A/mNm	
13	Slope of n-M curve	$\Delta n / \Delta M$	438	387	394	379	411	462	min ⁻¹ /mNm	
14	Rotor inductance	L	11	45	200	450	800	1 800	μ H	
15	Mechanical time constant	τ_m	11	11	11	11	11	11	ms	
16	Rotor inertia	J	2,4	2,7	2,7	2,8	2,6	2,3	gcm ²	
17	Angular acceleration	$\alpha_{max.}$	77	78	74	77	74	74	·10 ³ rad/s ²	
18	Thermal resistance	R_{th1} / R_{th2}	5 / 20						K/W	
19	Thermal time constant	τ_{w1} / τ_{w2}	6,8 / 440						s	
20	Operating temperature range:									
	– motor		-30 ... +85 (optional version -55 ... +125)						°C	
	– winding, max. permissible		+125						°C	
21	Shaft bearings		sintered bearings			ball bearings, preloaded				
22	Shaft load max.:		(standard)			(optional version)				
	– with shaft diameter		2			2			mm	
	– radial at 3 000 min ⁻¹ (3 mm from bearing)		1,5			8			N	
	– axial at 3 000 min ⁻¹		0,2			0,8			N	
	– axial at standstill		20			10			N	
23	Shaft play:									
	– radial		≤	0,03			0,015		mm	
	– axial		≤	0,2			0		mm	
24	Housing material		steel, black coated							
25	Mass		46						g	
26	Direction of rotation		clockwise, viewed from the front face							
27	Speed up to		$n_{max.}$	9 000						min ⁻¹
28	Number of pole pairs		1							
29	Magnet material		NdFeB							
Rated values for continuous operation										
30	Rated torque		M_N	2,2	4,5	6,7	6,8	6,6	6,1	mNm
31	Rated current (thermal limit)		I_N	0,7	0,7	0,52	0,37	0,25	0,16	A
32	Rated speed		n_N	7 170	6 390	4 390	4 800	4 300	4 060	min ⁻¹

Note: Rated values are calculated with nominal voltage and at a 22°C ambient temperature. The R_{th2} value has been reduced by 0%.

Note:

The diagram indicates the recommended speed in relation to the available torque at the output shaft for a given ambient temperature of 22°C.

The diagram shows the motor in a completely insulated as well as thermally coupled condition (R_{th2} 50% reduced).

The nominal voltage (U_N) curve shows the operating point at nominal voltage in the insulated and thermally coupled condition. Any points of operation above the curve at nominal voltage will require a higher operating voltage. Any points below the nominal voltage curve will require less voltage.



