

Transmitter



FEATURES

- Analog output $\pm 10\text{VDC}$, 0-20 or 4-20mA
- Serial communications: RS-485, MODBUS RTU protocol
- Internal resolution > 8000000 counts
- Relay outputs
- Compact DIN rail mounting
- CE compliant - EMC and Low Voltage

DESCRIPTION

AST 3P is a DIN rail mounted, high performance transmitter designed for applications with strain gauge transducers. It converts the output from connected loadcells into a very stable signal suitable for PC or PLC based control systems

AST 3P is typically used where a local display is essential either for displaying data or for front panel set-up. The set-up and calibration procedure is easily performed either from the front panel or by using the deltaCOM programme via a standard PC running under Windows 95/98/2000/NT4/ME/XP. All set-up data can be stored in the host computer and downloaded in case of replacement of the transmitter (full deltaCOM version is required).

The transmitter is fitted with two relay outputs having a response time of less than 20 msec. for use in high precision level control applications.


A unique and patented A/D converter, of high resolution and stability, serves as the heart of the transmitter. This advanced technology provides both analogue and serial outputs which can be conditioned to give the user accurate, stable and rapid response measurement information.

The AST 3P is compatible with other instruments in the Nobel programme and can communicate via standard RS-485/MODBUS RTU protocol with a common process control host - PC/PLC.

Fieldbus communication is possible via the GATE 3S module from Nobel.

The transmitter is CE marked, and fully compliant with the EMC and Low Voltage directives

CONFIGURATION




SPECIFICATION**TECHNICAL DATA****PERFORMANCE**

Resolution	8300000 counts
Conversion Speed	0.5 to 300Hz Accuracy 0.015%
Full Scale Range	$\pm 3.3\text{mV/V}$
Non-Linearity	$<0.005\%$ of used range
Excitation Voltage	8.8VDC to 5.5VDC with 1 to 8 of 350 ohm transducers, isolated 500V
No. of 350 Ω load cells	8 pcs (Total load > 45 ohms)
Filter	0.05 to 75Hz, type FIR, selectable bandwidth
Offset, drift	$<0.04\mu\text{V}/^\circ\text{C}$
Gain drift	$<0.0015\%$ of full scale
Calibration Methods	Data sheet, Table, Dead weight

ENVIRONMENTAL

Operating Temperature	- 10°C to + 50°C
Storage Temperature	- 25°C to + 85°C
Relative Humidity	95%
IP Level	IP 20

Setup Example**FRONT PANEL**

Display Type and Size	2 x 16 character LCD display with backlight
Keyboard	4 buttons for menu control and data entry

POWER SUPPLY

Voltage	24VDC $\pm 20\%$
Power Consumption	7W
Isolation	Digital inputs common with power supply. Other parts - 500V

ANALOG OUTPUT

Type	Isolated 16-bit bipolar D/A converter
Accuracy	0.04%
Non-Linearity	$<0.01\%$ of full scale
Gain Drift	$<0.003\%$ of full scale/ $^\circ\text{C}$
Filter	0.05 to 75Hz, type FIR, selectable bandwidth
Voltage	0-10 or $\pm 10\text{VDC}$
Load Data	min 500 ohm
Offset Drift	$<0.35\text{mV}/^\circ\text{C}$
Current	0-20mA, $\pm 20\text{mA}$, 4-20mA or - 12-20mA
Load Data	max 500 ohm
Offset Drift	$<0.7\mu\text{A}/^\circ\text{C}$

DIGITAL INPUTS

Inputs	2 pcs (option)
Type and Load	24VDC, 6mA

RELAY OUTPUTS

Number	2 pcs (each with 1 switching group)
Load	Max 1A, 30V AC or DC

COMMUNICATION INTERFACE

Interface	RS-485 (two-wires or four-wires), isolated 500V
Protocol	MODBUS RTU or ASCII
Baud Rate	Up to 115.2 kbaud
Function	For control communication (MODBUS RTU) or external display (ASCII)

MECHANICAL DATA

Dimensions	75 x 100 x 110mm (H x W x D)
Standard Mounting	DIN 46277 and DIN EN 50022
Connector Type	Plug-in screw terminals
Certifications	CE

Subject to change without notice.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase.

To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.