

WimTec® MULTI

Spare part



Matt chrome



White



Touch-free activation

Comfortable and hygienic operation thanks to automatic flushing.



Need-based pre-flush

The moistened urinal improves the flushing of the urine.



Adjustable main flush

Operators can precisely adjust the flushing duration to the urinal ceramics.



Intelligent stagnation flush

An automatic stagnation flush is performed whenever the fitting has not been used for 24 h, thus preventing an uncontrolled rise in the number of bacteria in the cold water system. In addition, the odour trap is restored.

Technical data:

WimTec MULTI - 230 V:

Supply voltage: 230 V 50 Hz
Power consumption: approx. 3 VA
Magnetic valve: 1/2" 24 V

WimTec MULTI - 9 V:

Battery: 9-V alkaline 6LR22 or 6LF22
Battery life: 9-V alkaline – approx. 100,000 flushings (max. 2 years)
Magnetic valve: 1/2" 6 V

Further technical data:

Detection range: adjustable from 30 - 70 cm
Pre-flush: after 1 s to 5 min of non-usage
Main flush: adjustable from 1 - 15 s
Stagnation flush: flushing interval: after 24 h of non-usage, flushing duration: as main flush
Flow pressure: 0.05 - 0.6 MPa (0.5 - 6 bar)
Static pressure: max. 0.8 MPa (8 bar)
Flow rate: approx. 0.3 to approx. 0.7 l/s at 0.3 MPa (3 bar) can be reduced acc. to EN 12541
Water inlet: R 1/2" IT
Water outlet: R 1/2" OT

Dimensions:

Front plate: W/H: 173 x 217 mm
Water outlet: R 1/2" OT

Material:

Front plate: plastic

Designation	Material	Art. no.	PG
-------------	----------	----------	----

WimTec MULTI - 230 V

Touch-free single urinal flush control for mains operation.

Delivery scope: Circuit board with integrated safety transformer, mounting frame, magnetic valve, **without flush-mount set.**

Matt chrome	100 211	1
White	100 204	1

WimTec MULTI - 9 V

Touch-free single urinal flush control for battery operation.

Delivery scope: Circuit board, battery module incl. 9-V battery, mounting frame, magnetic valve, **without flush-mount set.**

Matt chrome	100 426	1
White	100 419	1

Accessories and spare parts see page 200 onwards.