



DOUBLE HOOK

TEST
METHOD3x16
STAINLESSSTAINLESS
304
STEEL

RB-102



PAT



Installation

- Can be used as a light duty tie up cleat.

Item No.	Weight (g)	Box (pcs)	Carton (pcs)	Material	Finish
RB-102	16	40	400	304 Stainless Steel	Satin


ROTATING / SWING HOOK

TEST
METHODLOAD CAPACITY
6.1 kg
13 lbs3x25
STAINLESSSTAINLESS
304
STEEL



RF-U50



PAT



- Rotates 360° and swings 180°.
- Can be mounted in various directions.



Installation

Item No.	Load Capacity (kg)	Weight (g)	Box (pcs)	Carton (pcs)	Material	Finish
RF-U50	6.1 (13 lbs)	40	25	250	304 Stainless Steel	Satin


ROTATING HOOK

TEST
METHODLOAD CAPACITY
3 kg
6.6 lbs

NSF

3x25
STAINLESSSTAINLESS
304
STEEL

RF-50S





- Rotates 360°.
- Can be mounted in various directions.

Item No.	Load Capacity (kg)	Weight (g)	Box (pcs)	Carton (pcs)	Material	Finish
RF-50S	3 (6.6 lbs)	33	25	500	304 Stainless Steel	Satin

HOOK

TEST
METHODLOAD CAPACITY
8-10 kg
17.6-22 lbs3.5x16
STAINLESSSTAINLESS
304
STEEL

HJ



Installation

Material	Finish
304 Stainless Steel	Satin

Item No.	D	C	H	H ₁	A	B	Load Capacity (kg)	Weight (g)	Box (pcs)	Carton (pcs)
HJ-30S	32.5	20	32.5 (1-9/32")	13.5	16	17 (43/64")	8 (17.6 lbs)	15	30	600
HJ-50S	43.5	30	47 (1-27/32")	22	21	22 (7/8")	10 (22 lbs)	30	40	800